

ADIABATIC COMPRESSION IN A DIESEL ENGINE

Link to: [physicspages home page](#).

To leave a comment or report an error, please use the auxiliary blog.

Reference: Daniel V. Schroeder, *An Introduction to Thermal Physics*, (Addison-Wesley, 2000) - Problem 1.37.

As an example of adiabatic compression of an ideal gas, consider the compression of air in a diesel engine. Atmospheric air (at a temperature of, say, $10^\circ\text{C} = 283\text{ K}$) is quickly compressed to $\frac{1}{20}$ of its original volume. From the relation

$$VT^{f/2} = \text{constant} \quad (1)$$

where f is the number of degrees of freedom of a gas molecule, we can estimate the temperature of the air after compression. As most air molecules are diatomic, we can take $f = 5$ (3 translational + 2 rotational degrees of freedom; this assumes that vibrational modes are frozen out, although I'm not sure that's true for higher temperatures), so the temperature T_f after compression is

$$T_f = \left(\frac{V_i}{V_f}\right)^{2/f} T_i \quad (2)$$

$$= 20^{2/5} \times 283 \quad (3)$$

$$= 938\text{ K} \quad (4)$$

$$= 665^\circ\text{ C} \quad (5)$$

The autoignition temperature for diesel is 256° C so the fuel will automatically ignite when the air is compressed, which is why diesel engines don't need spark plugs.